


Antimony Resource increases 66% to 14,500t & Global MRE exceeds 1.4 Moz AuEq



Siren Gold Limited (ASX: **SNG**) (Siren or the Company) is pleased to provide an update on its **Auld Creek Project in Reefton**.

Highlights

- The updated Auld Creek Mineral Resource Estimate (MRE) has increased to **210koz @ 7.7g/t AuEq** containing **105koz @ 3.84g/t Au** and **14.5kt of antimony @ 1.7% Sb**.
- The updated Auld Creek MRE represents an **increase of 38koz (+58%) of gold** and **5.8kt (+66%) of antimony**.
- The MRE comprises the Fraternal and Bonanza East Shoots only and is based on existing surface trenches and includes the drilling carried out in early 2024.
- Resource is currently defined to approximately 150m below surface and remains open at depth.
- Siren's Reefton Project MRE now stands at **483koz of Au** and **14.5kt of Sb** for **588koz @ 4.7 g/t AuEq**.
- Siren's Global MRE (including Sams Creek) now stands at **1.31Moz of Au** and **14.5kt of Sb** for **1.41Moz @ 3.4 g/t AuEq** (100% basis).

Siren Managing Director and CEO, Victor Rajasooriar commented:

"The updated Reefton MRE of 588koz AuEq, positions the project to be further drilled and developed, with only a small drilling program having been carried out in 2024. The Auld Creek project has only been drilled to approximately 150m below surface and the potential to grow that further is outstanding given the mineralisation trend continues at depth. The antimony resource having increased by nearly 66% positions Reefton to be a potential supplier of antimony to western countries and could fast track New Zealand as the next producer of this critical mineral.

New Zealand has just produced a draft Critical Mineral List. Included on the list are minerals that will be used around the world to build technology, and support a clean energy transition, with Antimony ranked at No 5 on the list. The work being done by the New Zealand Government to map out minerals, classify which are critical, and develop a strategy to encourage growth and investment in mining is a big step forward for both the industry and the Country. This is a positive signal that New Zealand has a role in the global supply chain for critical minerals and the Company continues working with all stakeholders to extract full value from its Reefton Project".

Registered Address

Siren Gold Limited
Level 2
41 Ord Street
West Perth WA 6005
ASX: **SNG**
ACN: **619 211 826**

t: +61 8 6458 4200
e: admin@sirengold.com.au
w: sirengold.com.au

Corporate

Brian Rodan
Non-Executive
Chairman
Paul Angus
Technical Director

Victor Rajasooriar
Managing Director & CEO
Keith Murray
Non-Executive Director
Sebastian Andre
Company Secretary

Projects

Sams Creek Project
Reefton Project

Shares on Issue

207,173,894

Table 1. Siren's Reefton Mineral Resource Estimate.

Project	Status	Cut-off (g/t)	Tonnes (Mt)	Au (g/t)	Ounces (koz)	Sb (%)	Sb (Kt)	AuEq g/t	AuEq ¹ (koz)
Alexander River	Inferred	1.5	1.07	4.95	169.6			4.95	169.6
Big River	Inferred	1.5	0.83	3.94	105.5			3.94	105.5
Supreme	Inferred	1.5	1.05	2.71	103.3			2.71	103.3
Auld Creek ¹	Inferred	1.5	0.85	3.84	104.7	1.71	14.5	7.69	209.9
Total	Inferred	1.5	3.798	3.86	483.1	1.71	14.5	4.72	588.3

¹ Based on gold equivalent formula of AuEq = Au g/t + 2.25 x Sb% using a Au price of US\$2160/oz, Sb price of US\$15,625 per tonne and 85% recovery.

Table 2. Siren's Global Mineral Resource Estimate (100% basis)

Project	Status	Cut-off (g/t)	Tonnes (Mt)	Au (g/t)	Ounces (koz)	Sb (%)	Sb (Kt)	AuEq (g/t)	AuEq ² (koz)
Sams Creek ¹	Indicated	1.5	3.29	2.8	295.6			2.80	295.6
Total	Indicated	1.5	3.29	2.8	295.6			2.80	295.6
Sams Creek ¹	Inferred	1.5	5.81	2.83	528.8			2.83	528.8
Alexander River	Inferred	1.5	1.07	4.95	169.6			4.95	169.6
Big River	Inferred	1.5	0.83	3.94	105.5			3.94	105.5
Supreme	Inferred	1.5	1.05	2.71	103.3			2.71	103.3
Auld Creek	Inferred	1.5	0.85	3.84	104.7	1.71	14.5	7.69	209.9
Total	Inferred	1.5	9.61	3.24	1,011.9	1.71	14.5	3.58	1,117.1
Total	Indicated + Inferred	1.5	12.90	3.13	1,307.5	1.71	14.5	3.38	1,412.7

¹ Siren owns 81.9% of the Sams Creek Project.

² Based on gold equivalent formula of AuEq = Au g/t + 2.25 x Sb% using a Au price of US\$2160/oz, Sb price of US\$15,625 per tonne and 85% recovery.

Background

The Auld Creek Prospect is contained within Siren's Golden Point exploration permit and is situated between the Globe Progress mine, which historically produced **418koz @ 12.2g/t Au**, and the Crushington group of mines that produced **515koz @ 16.3g/t Au** (Figure 1). More recently OceanaGold (OGL) mined an open pit and extracted an additional 600koz of gold from lower grade remnant mineralisation around the historic Globe Progress mine. Collectively these mines produced **1.6Moz at 10g/t Au**.

In August 2023 (see Announcement date 21 August 2023) Siren estimated the Maiden Auld Creek MRE of **66koz @ 3.5g/t Au, 8,700t @ 1.5% Sb**. This estimate was for the **Fraternal Shoot** only.

Since the Maiden MRE was announced drilling at Auld Creek continued to largely target the Bonanza East Shoot (Figures 2 – 4). Significant drillhole intersections completed since the August 2023 maiden MRE are shown in Table 3.

For personal use only




Figure 1. Reefton area showing Auld Creek Project, and surrounding gold and coal mines.

For personal use only




Figure 2. Auld Creek drillhole plan and MRE limit.




Figure 3. Schematic Bonanza East Long section.




Figure 4. Schematic Fraternal Long section.

For personal use only

Table 3. Significant drillhole intersections since the Maiden MRE.

Hole ID	Shoot	From (m)	To (m)	Interval (m)	True Width (m) ¹	Au (g/t)	Sb (%)	AuEq (g/t) ²
ACDDH011	Bonanza East	78.3	83.4	5.1	3.0	4.1	7.0	19.9
		79.3	82.4	3.1	2.0	6.5	11.4	32.2
	Fraternal	145.3	147.0	1.7	1.0	3.6	1.3	6.5
ACDDH012	Bonanza East	18.7	23.7	5.0	4.0	2.1	0.0	2.1
ACDDH013	Bonanza East	29.0	33.5	4.5	4.5	1.6	1.7	5.4
		29.0	30.4	1.4	1.4	4.0	5.1	15.5
ACDDH014	Bonanza East	50.0	52.7	2.7	2.0	2.8	1.1	5.3
ACDDH015	Bonanza East	69.6	82.0	12.4	6.0	5.3	14.9	38.2
ACDDH015	Fraternal	105.0	128.0	23.0	8.0	4.0	0.2	4.5
ACDDH016	Bonanza East	67.0	89.2	22.2	10.0	7.3	0.3	8.0

¹ True widths are based on a sectional interpretation of the Fraternal mineralised zone dipping steeply (~85°) to the west and the Bonanza East mineralised zone dipping moderately (~55°) to the east. This dip may vary as more data becomes available and the true widths may change.

² Based on gold equivalent formula of $AuEq = Au\ g/t + 2.25 \times Sb\%$.

Updated Mineral Resource Estimate

Siren has completed an updated Auld Creek mineral resource estimate (MRE) based on an underground mining scenario. The MRE, which is in accordance with the JORC 2012 Code, has utilised geological and assay data from 3,340m of diamond core drilling from 27 drillholes and 11 trenches totalling 107.7m.

Siren is using a gold equivalent formula of $AuEq = Au\ g/t + 2.25 \times Sb\%$, based the average metal prices for the last 12 months of US\$2,160 per ounce of gold and US\$15,625 per tonne of antimony. Current prices are approximately US\$2,500 per ounce of gold and US\$25,000 per tonne of antimony. Metallurgical recoveries of 85% were used for both gold and antimony based on metallurgical testwork results announced in September 2024 (see *Announcement dated 05 September 2024*).

Details regarding the estimation of the Mineral Resources for the Auld Creek Project are provided in the attached JORC Table One.

Geology and Geological Interpretation

Geological interpretation is based on available field mapping data, structural mapping, drillhole lithology and grade data. Modelling was completed using Leapfrog Geo modelling software. Mark McCulloch carried out wireframing, geological modelling and estimation. Two mineralised grade domains were used based on the Fraternal and Bonanza East Shear Zones.

The mineralised domains were defined using both the drillholes and trenching in the database, intercepting the modelled mineralised domain. Geological mapping and trenching completed by Siren defined the surface trace of the mineralisation. Drillhole cross-sections and geology 3D modelling by Siren geologists were also used to guide the geological interpretation of the mineralised zones.

A nominal cut-off grade of 0.50g/t AuEq was used to guide the continuity of the mineralised wireframes; however, at the modelling geologist's discretion, intervals of 0.50 g/t AuEq were omitted from wireframes (e.g. at the periphery of mineralisation). The east-dipping Bonanza mineralised structure intercepts the Fraternal Shear and is included in the model.

Mineralisation domain wireframes were modelled using the Leapfrog Geo Vein System modelling technique. An oxide wireframe was designed based on the weathering logged in the drillholes. Density data for waste and mineralisation was collected during Siren's drilling programs at both Auld Creek and other Reefton gold projects. No densities were taken in weathered rock at Auld Creek. The geology is very similar to Siren's Big River and Alexander River Reefton projects, and oxide densities from these projects were used.

No historical mine workings are found in the Fraternal Shear, while the Bonanza East Shear has a single exploration drive, but the exact location of it is uncertain.

Sampling and Analysis

Selective sampling of drill core was completed where mineralisation was geologically logged with intervals selected for sampling were photographed and cut into half (along the axis of the core). Generally, 1m intervals were sampled, ensuring all orientation marks were retained. This methodology of sampling drill core is industry standard and deemed appropriate. Trench sampling was based on 1m intervals unless dictated by geology.

Estimation Methodology

For this resource estimate, Siren has completed the following:

- Geological interpretation and wireframing in Leapfrog Geo based on AuEq data;
- Hard boundary compositing in Leapfrog – Edge Module (Leapfrog Edge);
- Variography and Ordinary Kriging in Leapfrog Edge; and
- Block Model Estimation in Leapfrog.

Au and Sb were estimated individually, and the AuEq was calculated from these results. Composites for each element were based on 1m composites. Outlier grades were assessed by reviewing composite histograms of gold grades. Extreme outlier grades in Au in the Fraternal were identified, and this was controlled by using the Leapfrog outlier tool in estimation. Other variables and domains determined that no top-cut was required.

An estimation domain was created for the Fraternal and Bonanza East mineralisation shear zones. The hard boundary domains were based on a 0.5g/t AuEq cut-off.

Individual domain search distances, number of passes, minimum and maximum sample numbers, block size, variography and Exploration Data Analysis (EDA) are outlined in the Auld Creek Mineral Resource Estimate Report and summarised in JORC Table 1.

Block model validation included block statistics review, declustering means, swath plots, and visual inspection of grade distribution against composites. Sensitivities to block size, domain boundaries, and estimation parameters were undertaken.

Cut-off Grades

The MRE has been reported at a 1.5g/t Au cut-off grade, which Siren considers appropriate for an underground mining operation.

Siren is using a gold equivalent formula of $AuEq = Au_{g/t} + 2.25 \times Sb\%$, based the average metal prices for the last 12 months of US\$2,160 per ounce of gold and US\$15,625 per tonne of antimony.

Mining Factors

The MRE has been completed with the assumption that it will be mined using underground mining methods. No other detailed assumptions have been made to date. Metallurgical recoveries of 90% for

both gold and antimony based on metallurgical testwork results announced in September 2024 (see *Announcement dated 05 September 2024*).

Classification of Mineral Resource Confidence

The Auld Creek MRE has been classified by the independent Competent Person as 'Inferred' based on the current understanding of geological and grade continuity and drill density. The classification reflects the Competent Person's confidence in the location, quantity, grade, geological characteristics and continuity of the MRE. The MRE has been classified as Inferred based on the following relevant factors:

- Drillhole and trench spacing, and
- Structural controls and geological continuity

The data spacing and distribution are sufficient to establish geological and grade continuity appropriate for Mineral Resource estimation and classification, and the results appropriately reflect the Competent Person's view of the deposit.

The MRE with Au g/t, Sb % and AuEq g/t at a 0.0 g/t, 1.0g/t and 1.5g/t AuEq cut-offs are shown in Table 4. The MRE split by domain at a 1.5g/t cut-off is shown in Table 5. Images of the block model for AuEq are shown in Figures 4 and 5.

The updated Auld Creek MRE represents an **increase of 38koz (+58%) of gold** and **5.8kt (+66%) of antimony**.

Table 4. Auld Creek Mineral Resource Estimate at various cut-offs.

AuEq Cut-off (g/t)	Status	Tonnes (kt)	Au (g/t)	Ounces (koz)	Sb%	Sb (kt)	AuEq (g/t)	AuEq (koz)
0.0	Inferred	985.5	3.45	109.4	1.47	14.6	6.78	215.0
1.0	Inferred	954.7	3.54	108.6	1.53	14.6	6.98	214.2
1.5	Inferred	848.5	3.84	104.6	1.71	14.5	7.69	209.9

Table 5. Auld Creek Mineral Resource Estimate at 1.5g/t cut-off.

Domain	Status	Tonnes (kt)	Au (g/t)	Ounces (koz)	Sb (%)	Sb (kt)	AuEq (g/t)	AuEq (koz)
Fraternal	Inferred	614.1	3.91	77.2	1.41	8.7	7.10	104.2
Bonanza East	Inferred	234.4	3.64	27.4	2.49	5.8	9.25	69.7
Total	Inferred	848.5	3.84	104.6	1.71	14.5	7.69	209.9




Figure 5. Fraternal Long Section with AuEq block model overlaid.




Figure 6. Bonanza East Long Section with AuEq block model overlaid.

For personal use only

This announcement has been authorised by the Board of Siren Gold Limited

Enquiries

For more information contact:

Victor Rajasooriar
Managing Director
+61 8 6458 4200

Competent Person Statement

The information in this announcement that relates to exploration results, and any exploration targets, is based on, and fairly represents, information and supporting documentation prepared by Mr Paul Angus, a competent person who is a member of the Australasian Institute of Mining and Metallurgy. Mr Angus has a minimum of five years' experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a competent person as defined in the 2012 Edition of the Joint Ore Reserves Committee Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Mr Angus is a related party of the Company, being the Technical Director, and holds securities in the Company. Mr Angus has consented to the inclusion in this announcement of the matters based on his information in the form and context in which it appears.

The information in this announcement that relates to the Auld Creek MRE is based on, and fairly represents, information and supporting documentation prepared by Mr Mark McCulloch, a Chartered Professional of the Australasian Institute of Mining and Metallurgy. Mr McCulloch has a significant relevant experience in relation to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a competent person as defined in the 2012 Edition of the Joint Ore Reserves Committee Australasian Code for Reporting of Exploration Results. Mr McCulloch has consented to the inclusion in this announcement of the matters based on his information in the form and context in which it appears.

For personal use only

JORC Code, 2012 Edition – Table 1

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

	JORC Code Explanation	Commentary
<p><i>Sampling techniques</i></p>	<ul style="list-style-type: none"> • <i>Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i> • <i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i> • <i>Aspects of the determination of mineralisation that are Material to the Public Report.</i> • <i>In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information.</i> 	<ul style="list-style-type: none"> • Siren Gold Limited (Siren), Oceana Gold Corporation (OGL) & Macraes Mining Co Ltd (MMCL) diamond core (DC) was used to obtain samples for geological logging and sampling. • Siren & OGL DC core samples were spilt in half using a core saw at 1m intervals unless determined by lithology i.e. Quartz vein contacts. • OGL completed 5m composited grind samples through barren host rock and assayed only for Au. • CRAE and MMCL channel and trench samples were based on 1m sample lengths with sample size and collection method is unknown. • OGL DC samples were pulverised to >95% passing 75µm to produce a 50g charge for fire assay for Au. • Siren trench sampling was taken based on 1m samples unless determined by lithology or mineralisation. <i>In situ</i> rock samples collected by geology hammer with average sample size of 2 kg. • Soil sampling was completed by hand auger or spade by CRAE. Macraes Mining Co Ltd (MMCL) used both hand auger & wacker drill for soil sampling. OGL collected soil samples by wacker drill, collecting around 300-500g samples. SIREN used a hand auger to collect a 300-400g sample of B-C horizon.
<p><i>Drilling techniques</i></p>	<ul style="list-style-type: none"> • <i>Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g. core</i> 	<ul style="list-style-type: none"> • Diamond drilling with DC diameters included PQ (96mm), HQ (63mm and NQ (47.6mm) and OGL & SIREN drilling is triple tubed using CS1000 or LF70 heli-rigs. • 2013 OGL drilling trailed open holing with a Strata-Pac collar for 50.6m in RDD0091.

For personal use only

	JORC Code Explanation	Commentary
	<p>diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</p>	<ul style="list-style-type: none"> All drilling has been helicopter-supported.
<p>Drill sample recovery</p>	<ul style="list-style-type: none"> Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	<ul style="list-style-type: none"> Full run and geotechnical logging with total core recoveries, RQD and core loss has been recorded by 1m for OGL 2007 & 2011 drilling. Siren recorded full run and geotechnical logging with total core recoveries, RQD and core lost as well as core orientation quality. Core recoveries for OGL were good. Highly shattered rock around puggy fault gouge zones are the areas where core loss can occur. No noticeable losses were observed by OGL or by Siren. ACDDH010 in the Bonanza East intercepted the mineralisation zone in the weathered zone and suffered significant core loss (Core recovery 69% in mineralisation). The hole was twinned by ACDDH012 with good recovery.
<p>Logging</p>	<ul style="list-style-type: none"> Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	<ul style="list-style-type: none"> All DC for OGL were logged for lithology, weathering, bedding, structure, alteration, mineralisation, jointing, colour and grain size using a standard set of inhouse logging codes and a template that was very similar to previous logging by OceanaGold (OGL) exploration programs. The logging method is quantitative. Logging entered into an acQuire database. OGL reported all core trays were photographed before core being sampled. MMCL logging was completed on paper and entered into the OGL acQuire database. Hard copies of these logs are complete. Siren trench and DC logging are based on core logging templates with similar quantitative data captured as OGL with a logging SOP. Photos are taken of the trench and each trench sample.
<p>Sub-sampling techniques and sample preparation</p>	<ul style="list-style-type: none"> If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to 	<ul style="list-style-type: none"> DC sample intervals were marked on the core, which was cut in half length ways with a diamond saw. Half the core was taken for the laboratory sample and the remaining core was archived. DC sampling was based on 1m lengths as well as allowing for geology. Laboratory duplicates and laboratory repeats were collected and assayed. The DC (2-3kg) and channel (1-2kg) sample sizes are considered appropriate to the grain and particle size for representative sampling. OGL completed 5m composited grind samples in barren host rock. Any grind samples that returned anomalous mineralisation (equivalent to at least 1m at 0.5 g/t Au), then had the equivalent core intervals cut in half and submitted to the laboratory as one metre half core samples.

	JORC Code Explanation	Commentary
	<p><i>maximise representativity of samples.</i></p> <ul style="list-style-type: none"> • <i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i> • <i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i> 	<ul style="list-style-type: none"> • MMCL sampling SOP for DC is not recorded, but DC sample lengths varied from 2m in barren rock to 1m in mineralised core. • Siren trench sample length is based on 1m with field duplicates taken on 1:20 samples.
<p><i>Quality of assay data and laboratory tests</i></p>	<ul style="list-style-type: none"> • <i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i> • <i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc</i> • <i>Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</i> 	<ul style="list-style-type: none"> • CRAE tested their soils for Au (ppb) As, Cu, Pb and Zn by Fire assay. CRAE tested their trench samples for Au, As & Sb. • MMCL stream sediment samples were analysed for Au (>1 ppb Au detection limit), Ag, As, Ba, Bi, Cd, Co, Cu, Mo, Pb, Sb, and Zn. • 1996 MMCL DC were tested for Au, As, Sb, Cu, Pb & Zn. Their trenching & soil samples were processed by ALS for a suite that included Au (>1 ppb Au), As, Bi, Ca, Cu, Fe, Mn, Mo, Pb, Sb, and Zn. • OGL 2007 DC samples were set to Amdel Laboratories in Macraes Flat, NZ for Au, As & Sb. • 2011 OGL DC and Channel samples are sent to SGS New Zealand. SGS laboratories carry a full QAQC program and are ISO 19011 certified where they were assayed by 50g fire assay. • OGL DC & wacker submissions included at least 2 Au Rocklab standards, 1 blank, laboratory duplicates and lab repeats were recorded. • 2011 Au results were completed at Reefton SGS mine lab while As and Sb were analysed at SGS Westport. Sb was analysed by XRF pressed powder pellet. Over limit method for Sb is unknown. • Sample preparation of OGL's DC at SGS comprised of drying, crushing, splitting (if required) and pulverising to obtain analytical sample of 250g with >95% passing 75 µm. • 2013 OGL included at least 1 certified standard and 2 blanks as well as at least 2 duplicates and were tested at SGS Reefton & Westport for Au, As & Sb. Sb was analysed by XRF pressed powder pellet. • OGL reviewed their results based on the performance of their certified standards results. If both standard assays from the same batch returned assay values outside two standard deviations of the actual value, the laboratory was requested to re-assay the job. • Siren re-assayed RRD087 and SIREN trenches have been assayed using SGS, New Zealand using FAM303 with 30g fire assay and AAS finish for Au. 42 multielement suite are then analysed by an Olympus Vanta pXRF on the <75µm pulps received from SGS. Sb is included which has a lower detection limit of 5ppm. • Siren samples are submitted with blanks, duplicates, lab repeats and CRM for Au analysis as well as full QAQC program of blanks, standards, repeats & duplicates during pXRF multielement analysis of the pulps. • 2011 wacker soil samples were sent to ALS Brisbane for 8 elements suite while rock chip samples were sent to SGS for Au, As & Sb. • Siren soil samples are sent to SGS New Zealand for Au 30g fire assay analysis for ppb

	JORC Code Explanation	Commentary
		<p>detection limits. The pulp is returned for a full analysis completed by Olympus Vanta pXRF with full QAQC. Preliminary soil sample analysis after the sample is dried in the oven for >6 hours at 100°C before the samples are sent to SGS.</p> <ul style="list-style-type: none"> • 2023 Siren DC and Channel samples are sent to SGS New Zealand. SGS laboratories carry a full QAQC program and are ISO 19011 certified where they were assayed by 30g fire assay. Screen Fire Assays are undertaken if there is visible gold. Pulps from the laboratory are analysed by RRL with a pXRF. • Antimony is analysed by pXRF with round robin check samples sent to ALS Brisbane where they are analysed by XRF.
<p><i>Verification of sampling and assaying</i></p>	<ul style="list-style-type: none"> • <i>The verification of significant intersections by either independent or alternative company personnel.</i> • <i>The use of twinned holes.</i> • <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> • <i>Discuss any adjustment to assay data.</i> 	<ul style="list-style-type: none"> • Hard copies of the results for 1996 exploration by MMCL were entered into acQuire database by OGL. • All laboratory assay results were received by OGL were stored in an acQuire database and laboratory signed PDF lab certificates for 2013 have been submitted to NZPAM. • Siren data is stored in excel, Dropbox and Leapfrog. The data storage system is basic but robust. • All SGS assay results received by SIREN are signed PDF lab certificates hard copies that are stored. • The data and future work will be stored and managed on a commercial database with inbuilt validation protocols in the future. • OGL completed RDD0081 and RDD0081A which are 3m apart. • Siren completed ACDDH010 and 012, which are 3-5m apart. • Siren quarter core results were combined to create an equal weight assay result for Au.
<p><i>Location of data points</i></p>	<ul style="list-style-type: none"> • <i>Accuracy and quality of surveys used to locate drillholes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i> • <i>Specification of the grid system used.</i> • <i>Quality and adequacy of topographic control.</i> 	<ul style="list-style-type: none"> • OGL used handheld GPS for placing and picking up the drill hole collars with series RDD00* while MMCL drill holes with the prefix of 96DDA* All drill holes were picked up by Chris Coll, a registered surveyor. • Siren place capped PVC drill hole collars down place, dip & orientation of each hole. OGL placed a single waratah with collars labelled on tags or PVC over per drill pad. MMCL placed a single waratah for each hole. • OGL & MMCL used New Zealand Map Grid (NZMG). • Siren used handheld Garmin 64s to pick up trenches, check old pad sites and mapping. • Trenches involved in the MRE were picked up by Chris Cole • The data has been translated into Transverse Mercator 2000 (NZTM). • Downhole surveys were taken every 50m in 2007 and 30m in 2011 & 2103 OGL drill programs. • Siren used a Precision downhole gyro for 15m surveys. • 1996 drilling by Macraes Limited completed a downhole survey around 30-45m intervals. • Relative level (RL) is calculated as above Sea Level. • Siren trenches are surveyed at the collar and azimuth and dip are taken at any changes along the trench length.

	JORC Code Explanation	Commentary
<p><i>Data spacing and distribution</i></p>	<ul style="list-style-type: none"> • <i>Data spacing for reporting of Exploration Results.</i> • <i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i> • <i>Whether sample compositing has been applied.</i> 	<ul style="list-style-type: none"> • Drilling directions and distances were variable because of the terrain and orientation of the target reef system but were within 25 to 100m spacing at the Fraternal and Bonanza East zones. • Some pads had multiple drilling fanning from them.
<p><i>Orientation of data in relation to geological structure</i></p>	<ul style="list-style-type: none"> • <i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i> • <i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i> 	<ul style="list-style-type: none"> • Drilling design was planned to intercept the mineralisation at high angles, but with drilling multiple holes from a single heli-drill pad into a very steep dipping reef zone, mineralisation was intercepted at a lower angle when drilling down dip.
<p><i>Sample security</i></p>	<ul style="list-style-type: none"> • <i>The measures taken to ensure sample security.</i> 	<ul style="list-style-type: none"> • OGL DC, soil and trench samples taken for the purposes of laboratory analysis were securely packaged on site and transported to the relevant laboratories by OGL. • MMCL and CRAE did not record their sample security processes. • Siren samples are stored in a locked core shed until despatch. Samples are transported to SGS, Westport by Siren.
<p><i>Audits or reviews</i></p>	<ul style="list-style-type: none"> • <i>The results of any audits or reviews of sampling techniques and data.</i> 	<ul style="list-style-type: none"> • No review of sampling techniques and data of recent sampling has been undertaken yet at the Auld Creek project. Big River and Alexander Projects have been independently reviewed by Measured Group. • Successful field checks by Siren have been completed to find OGL, MMCL & CRAE drill pad and trenching locations.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code Explanation	Commentary
<i>Mineral tenement and land tenure status</i>	<ul style="list-style-type: none"> Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	<ul style="list-style-type: none"> The Auld Creek Project (ACP) is within the permit EP 60-648 is a total of 4622 hectares in size and was granted to Reefton Resources Pty Limited (RRL) (a wholly owned subsidiary of Siren for a period of 5 years, expiring in March 2026. The ACP is located 4km south of the township of Reefton on the West Coast of New Zealand. The boundary of the Prospect is delineated by the catchment of Auld Creek which drains northwest into the Inangahua River. The ACP is immediately north of the rehabilitated Globe Progress Mine, which produced 418koz @ 12.2 g/t Au historically. 1km to the northeast, across the Inangahua River, the Crushington Gold Mining District historically produced 515koz @ 16.3 g/t Au. ACP is situated within Department of Conservation administrated land.
<i>Exploration done by other parties</i>	<ul style="list-style-type: none"> Acknowledgment and appraisal of exploration by other parties. 	<ul style="list-style-type: none"> Auld Creek mineralisation was found in 1870 where an adit was developed, with further adit and shaft developed 1908 and 1914. In 1930's the Department of Scientific Industrial & Research (DSIR) conducted an IP survey over the area. In 1970-71, Lime and Marble explored primarily for Sb with a soil sample program over the old workings which delineated two zones of anomalous Sb. CRAE explored the greater Reefton Goldfield including the Auld Creek project. In the 1980's they completed an extensive soil grid followed by collection of 118 rock chip, float, and trench samples. CRAE completed two ground magnetic surveys over the area attempting to locate a magnetic response from the shear zone and concluded that drilling was needed. CRAE focus and budget at the time moved into drilling the Globe Progress deposit just to the south. MMCL explored the project from 1994 to 2000 and undertook stream sediment sampling, infilled the central section of CRAE soil grid with several anomalous zones highlighted. MMCL completed wacker sampling in the southern portion where there is a thin glacial cover on the ridges. MMCL completed 109m of trenching to help generate drilling targets in the Bonanza and Fraternal zones. MMCL drilled 3 diamond holes with 96DDAC001 and 96DDAC002 targeting Fraternal and 96DDAC003 drilling into the Bonanza zone with a total of 324.6m OGL begun work in the project area in 2007 with a 3 diamond drillhole program (RDD0044, 045 & 59) to test the southern areas of the permit based on soil anomalies and structures extending from Globe Progress.

For personal use only

Criteria	JORC Code Explanation	Commentary
		<ul style="list-style-type: none"> • From 2008 to 2010 OGL completed mapping and wacker soil sampling program into Auld Creek North extending CRAE's soil grid another 400m. • In 2010 OGL completed another wacker program into the Fraternal & Bonanza zones overlapping previous work. • OGL then completed 7 diamond holes in 2010-11 to test southern extents of Fraternal zone completing 801.7m into a mineralised, steep westerly dipping zone ranging from 1m to 15m thick. • OGL completed an in house inferred resource of 0.17 Mt @ 2.60 g/t Au for 14,300 oz Au using 5 drillholes at the Fraternal deposit. • OGL completed a regional exploration drill hole (RDD0084) which was drilled into the southeast of the project area testing an Au+ As wacker anomaly. It returned a 1m @ 2.54 g/t Au which has not been followed up. • In 2013 OGL completed 3 more diamond holes into the Fraternal prospect for a total of 513.1m testing the down dip extents of the northern and central zones.
Geology	<ul style="list-style-type: none"> • <i>Deposit type, geological setting and style of mineralisation.</i> 	<ul style="list-style-type: none"> • Gold mineralisation in the Reefton Goldfield is structurally controlled; the formation of the different deposit types is interpreted to be due to focussing of the same hydrothermal fluid into different structural settings during a single gold mineralisation event, however, some of the deposits (e.g. Globe-Progress, Big River) appear to have been re-worked, with gold and sulphide mineral remobilisation having occurred during a later phase of brittle deformation. • In general, two end members of mineralisation styles exist, the "Blackwater Style" is comprised of relatively undeformed quartz lodes; whilst the "Globe-Progress Style" comprises highly deformed quartz - pug breccia material with a halo of disseminated sulphide mineralisation. • Three main structural deposit types appear to occur in the Reefton Goldfield. The Globe-Progress deposit occupies a distinct structural setting, where there is a clear break in the continuity and tightness of early folding. This break defines the east-west striking Globe-Progress shear zone. The fault splays off the Oriental-General Gordon shear zone. The geometry of the fault structure has allowed dilation and quartz vein deposition more or less contemporaneously with shearing, hydrothermal alteration, and low-grade mineralisation of the wall rocks. The broad disseminated mineralisation that now surrounds the Globe-Progress ore body is thought to have been formed by later movement on fault planes, in the presence of fluids, which led to some mobilisation and recrystallisation of metals and formed the halo of mineralised country rock. The Big River deposit shows similar paragenesis to Globe-Progress, except for the fact that the disseminated sulphide halo is not as extensive. • The second structural deposit type hosts most gold deposits i.e. Big River South, Scotia, Gallant and Crushington, however, these are typically small, narrow, steeply-plunging and consequently generally sub-economic. These deposits have formed in reverse shear zones that are parallel or sub-parallel to cleavage and bedding. The attitude of these deposits has not allowed the formation of significant shear zones, dilatant zones or fluid channel ways and

Criteria	JORC Code Explanation	Commentary																																																																																																																																																										
		<p>consequently the deposits formed tend to be small. Most mineralised zones occur as small-scale versions of the other two deposit types, formed in small, localised transgressive structural settings that are conducive to those deposit types.</p> <ul style="list-style-type: none"> The third deposit type occurs as steeply dipping transgressive dilatant structures, which are typically northeast trending (Blackwater). Gold mineralisation is interpreted to have formed when an earlier, favourably orientated shear zone became a zone of weakness under strike-slip movement. This dextral strike-slip movement created a locus for dilation and fluid channelling caused by periodic fluid pumping and over pressuring during the hydrothermal mineralising event. Auld Creek mineralisation found at Bonanza and Fraternal is interpreted as like the second structural type as listed above and associated with a major shear zone hosted close or within an anticline. 																																																																																																																																																										
Drillhole Information	<ul style="list-style-type: none"> A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drillholes: <ul style="list-style-type: none"> easting and northing of the drillhole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drillhole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	<p>ACP drillhole details:</p> <table border="1"> <thead> <tr> <th>Hole ID</th> <th>NZTM E</th> <th>NZTM N</th> <th>RL</th> <th>Total Depth (m)</th> <th>Dip</th> <th>Azimuth (true)</th> </tr> </thead> <tbody> <tr><td>96DDAC001</td><td>1507211</td><td>5333156</td><td>528</td><td>70.1</td><td>-70</td><td>60</td></tr> <tr><td>96DDAC002</td><td>1507211</td><td>5333156</td><td>528</td><td>84.0</td><td>-75</td><td>70</td></tr> <tr><td>96DDAC003</td><td>1507129</td><td>5333155</td><td>532</td><td>170.5</td><td>-65</td><td>70</td></tr> <tr><td>RDD0044</td><td>1507830</td><td>5331978</td><td>612</td><td>60.6</td><td>-60</td><td>90</td></tr> <tr><td>RDD0045</td><td>1507687</td><td>5332133</td><td>608</td><td>67.7</td><td>-60</td><td>90</td></tr> <tr><td>RDD0059</td><td>1507705</td><td>5332243</td><td>568</td><td>100.3</td><td>-60</td><td>90</td></tr> <tr><td>RDD0081</td><td>1507216</td><td>5333070</td><td>559</td><td>75.9</td><td>-60</td><td>35</td></tr> <tr><td>RDD0081A</td><td>1507216</td><td>5333070</td><td>559</td><td>151.5</td><td>-60</td><td>35</td></tr> <tr><td>RDD0084</td><td>1507782</td><td>5332707</td><td>577</td><td>148.1</td><td>-60</td><td>270</td></tr> <tr><td>RDD0085</td><td>1507216</td><td>5333070</td><td>559</td><td>79.0</td><td>-60</td><td>110</td></tr> <tr><td>RDD0086</td><td>1507216</td><td>5333070</td><td>559</td><td>141.5</td><td>-60</td><td>150</td></tr> <tr><td>RDD0087</td><td>1507216</td><td>5333070</td><td>559</td><td>132.5</td><td>-75</td><td>75</td></tr> <tr><td>RDD0088</td><td>1507290</td><td>5333147</td><td>539</td><td>159.5</td><td>-60</td><td>270</td></tr> <tr><td>RDD0089</td><td>1507208</td><td>5333135</td><td>535</td><td>61.8</td><td>-52</td><td>90</td></tr> <tr><td>RDD0091</td><td>1507290</td><td>5333147</td><td>539</td><td>166.5</td><td>-52</td><td>230</td></tr> <tr><td>RDD0092</td><td>1507290</td><td>5333147</td><td>539</td><td>161.1</td><td>-62</td><td>230</td></tr> <tr><td>RDD0093</td><td>1507290</td><td>5333147</td><td>539</td><td>185.5</td><td>-55</td><td>215</td></tr> <tr><td>ACDDH004</td><td>1507198</td><td>5332970</td><td>605</td><td>142.6</td><td>-60</td><td>045</td></tr> <tr><td>ACDDH005</td><td>1507198</td><td>5332970</td><td>605</td><td>147.4</td><td>-60</td><td>100</td></tr> <tr><td>ACDDH006</td><td>1507198</td><td>5332970</td><td>605</td><td>177.4</td><td>-75</td><td>090</td></tr> <tr><td>ACDDH007</td><td>1507185</td><td>5332877</td><td>604</td><td>154.3</td><td>-58</td><td>040</td></tr> </tbody> </table>	Hole ID	NZTM E	NZTM N	RL	Total Depth (m)	Dip	Azimuth (true)	96DDAC001	1507211	5333156	528	70.1	-70	60	96DDAC002	1507211	5333156	528	84.0	-75	70	96DDAC003	1507129	5333155	532	170.5	-65	70	RDD0044	1507830	5331978	612	60.6	-60	90	RDD0045	1507687	5332133	608	67.7	-60	90	RDD0059	1507705	5332243	568	100.3	-60	90	RDD0081	1507216	5333070	559	75.9	-60	35	RDD0081A	1507216	5333070	559	151.5	-60	35	RDD0084	1507782	5332707	577	148.1	-60	270	RDD0085	1507216	5333070	559	79.0	-60	110	RDD0086	1507216	5333070	559	141.5	-60	150	RDD0087	1507216	5333070	559	132.5	-75	75	RDD0088	1507290	5333147	539	159.5	-60	270	RDD0089	1507208	5333135	535	61.8	-52	90	RDD0091	1507290	5333147	539	166.5	-52	230	RDD0092	1507290	5333147	539	161.1	-62	230	RDD0093	1507290	5333147	539	185.5	-55	215	ACDDH004	1507198	5332970	605	142.6	-60	045	ACDDH005	1507198	5332970	605	147.4	-60	100	ACDDH006	1507198	5332970	605	177.4	-75	090	ACDDH007	1507185	5332877	604	154.3	-58	040
Hole ID	NZTM E	NZTM N	RL	Total Depth (m)	Dip	Azimuth (true)																																																																																																																																																						
96DDAC001	1507211	5333156	528	70.1	-70	60																																																																																																																																																						
96DDAC002	1507211	5333156	528	84.0	-75	70																																																																																																																																																						
96DDAC003	1507129	5333155	532	170.5	-65	70																																																																																																																																																						
RDD0044	1507830	5331978	612	60.6	-60	90																																																																																																																																																						
RDD0045	1507687	5332133	608	67.7	-60	90																																																																																																																																																						
RDD0059	1507705	5332243	568	100.3	-60	90																																																																																																																																																						
RDD0081	1507216	5333070	559	75.9	-60	35																																																																																																																																																						
RDD0081A	1507216	5333070	559	151.5	-60	35																																																																																																																																																						
RDD0084	1507782	5332707	577	148.1	-60	270																																																																																																																																																						
RDD0085	1507216	5333070	559	79.0	-60	110																																																																																																																																																						
RDD0086	1507216	5333070	559	141.5	-60	150																																																																																																																																																						
RDD0087	1507216	5333070	559	132.5	-75	75																																																																																																																																																						
RDD0088	1507290	5333147	539	159.5	-60	270																																																																																																																																																						
RDD0089	1507208	5333135	535	61.8	-52	90																																																																																																																																																						
RDD0091	1507290	5333147	539	166.5	-52	230																																																																																																																																																						
RDD0092	1507290	5333147	539	161.1	-62	230																																																																																																																																																						
RDD0093	1507290	5333147	539	185.5	-55	215																																																																																																																																																						
ACDDH004	1507198	5332970	605	142.6	-60	045																																																																																																																																																						
ACDDH005	1507198	5332970	605	147.4	-60	100																																																																																																																																																						
ACDDH006	1507198	5332970	605	177.4	-75	090																																																																																																																																																						
ACDDH007	1507185	5332877	604	154.3	-58	040																																																																																																																																																						

For personal use only

Criteria	JORC Code Explanation	Commentary						
		ACDDH008	1507185	5332877	604	110.0	-58	100
		ACDDH009	1507185	5332877	604	181.5	-74	135
		ACDDH010	1507215	5333070	560	40.8	-60	270
		ACDDH011	1507215	5333070	560	161.0	-81	130
		ACDDH012	1507215	5333070	560	39.2	-65	270
		ACDDH013	1507208	5333135	533	52.0	-50	255
		ACDDH014	1507208	5333135	533	70.4	-90	255
		ACDDH015	1507208	5333135	533	136.0	-58	158
		ACDDH016	1507208	5333135	533	101.9	-55	330
		ACDDH017	1507085	5333091	582	060	-55	100
		ACDDH018	1507085	5333091	582	115	-50	270
		ACDDH019	1507085	5333091	582	105	-78	130
		ACDDH020	1507212	5333199	510	300	-72	100
		ACDDH021	1507212	5333199	510	195	-76	110
		TOTAL				4,320.4		
Significant ACP diamond drillhole intercepts								
Hole ID	Mineralised Zone	From	To	Interval (m)	True Width (m) ¹	Au g/t	Sb %	
96DDAC001	Fraternal	51.9	53.1	1.2	0.6	1.0	7.9	
RDD0081	Fraternal	45.0	51.0	6.0	3.0	1.7	2.0	
	Fraternal	57.0	67.0	11.0	6.0	2.2	0.1	
RDD0081a	Fraternal	57.0	67.0	10.0	5.5	1.7	0.1	
RDD0085	Fraternal	30.0	64.0	34.0	20.5	1.6	0.7	
Incl		30.0	37.0	7.0	4.5	3.0	3.2	
Incl		43.0	51.0	8.0	5.2	2.6	0.2	
Incl		59.0	64.0	5.0	3.4	1.6	0.0	
RDD0087	Fraternal	63.0	98.0	35.0	12.0	4.1	2.9	
Incl		63.0	81.0	18.0	5.5	5.7	4.8	
RDD0088	Fraternal	125.0	127.0	2.0	1.4	1.3	2.9	
ACDDH004	Bonanza East	53.3	55.9	2.6	2.0	4.3	0.0	
ACDDH004	Fraternal	116.2	136.8	20.6	13.0	5.9	2.6	
Incl		116.2	120.8	4.6	3.0	10.7	3.9	
ACDDH005	Fraternal	59.4	77.3	17.9	12.0	2.3	0.1	

Criteria	JORC Code Explanation	Commentary																																																																																							
		Incl		59.4	63.3	3.9	2.6	3.3	0.1																																																																																
		Incl		67.3	77.3	10.0	6.7	2.8	0.1																																																																																
		ACDDH006	Fraternal	147.5	156.1	8.6	4.0	1.3	0.2																																																																																
		Incl		147.5	150.4	3.1	2.0	1.7	0.5																																																																																
		ACDDH007	Fraternal	124.0	150.5	26.5	15.0	2.7	0.1																																																																																
		Incl		133.0	150.5	17.5	9.0	3.7	0.1																																																																																
		Incl		142.0	148.5	8.5	4.5	6.7	0.0																																																																																
		Incl		142.0	148.5	6.5	3.7	8.5	0.0																																																																																
		ACDDH008	Fraternal	72.1	76.3	4.2	4.0	1.5	0.0																																																																																
		ACDDH009	Fraternal	118.7	124.2	5.5	2.7	1.1	0.0																																																																																
		ACDDH011	Bonanza East	78.3	83.4	5.1	3.0	4.1	7.0																																																																																
				79.3	82.4	3.1	2.0	6.5	11.4																																																																																
			Fraternal	145.3	147.0	1.7	1.0	3.6	1.3																																																																																
		ACDDH012	Bonanza East	18.7	23.7	5.0	4.0	2.1	0.0																																																																																
		ACDDH013	Bonanza East	29.0	33.5	4.5	4.5	1.6	1.7																																																																																
				29.0	30.4	1.4	1.4	4.0	5.1																																																																																
		ACDDH014	Bonanza East	50.0	52.7	2.7	2.0	2.8	1.1																																																																																
		ACDDH015	Bonanza East	69.6	82.0	12.4	6.0	5.3	14.9																																																																																
			Fraternal	105.0	128.0	23.0	8.0	4.0	0.2																																																																																
		ACDDH016	Bonanza East	67.0	89.15	22.15	10.0	7.3	0.3																																																																																
<p>¹ True widths are based on a sectional interpretation of the Fraternal mineralised zone dipping steeply (~85°) to the west and the Bonanza East mineralised zone dipping moderately (~55°) to the east. This dip may vary as more data becomes available and the true widths may change.</p> <p>ACP trench details:</p> <table border="1"> <thead> <tr> <th>Trench</th> <th>Zone</th> <th>NZTM_E</th> <th>NZTM_N</th> <th>Elev</th> <th>Length</th> <th>Dip</th> <th>Azimuth</th> </tr> </thead> <tbody> <tr> <td>FTTR001</td> <td>Fraternal</td> <td>1507244</td> <td>5333083</td> <td>541</td> <td>8</td> <td>0</td> <td>281</td> </tr> <tr> <td>FTTR002</td> <td>Fraternal</td> <td>1507237</td> <td>5333081</td> <td>543</td> <td>1.5</td> <td>0</td> <td>189</td> </tr> <tr> <td>FTTR003</td> <td>Fraternal</td> <td>1507235</td> <td>5333167</td> <td>519</td> <td>7</td> <td>0</td> <td>273</td> </tr> <tr> <td>FTTR004</td> <td>Fraternal Nth</td> <td>1507261</td> <td>5333361</td> <td>467</td> <td>5</td> <td>0</td> <td>80</td> </tr> <tr> <td>FTTR005</td> <td>Fraternal</td> <td>1507234</td> <td>5333031</td> <td>573</td> <td>9.8</td> <td>0</td> <td>60</td> </tr> <tr> <td>FTTR006</td> <td>Fraternal</td> <td>1507232</td> <td>5333306</td> <td>479</td> <td>5.6</td> <td>-40</td> <td>110</td> </tr> <tr> <td>FTTR007</td> <td>Fraternal Nth</td> <td>1507177</td> <td>5333243</td> <td>577</td> <td>7.7</td> <td>-20</td> <td>95</td> </tr> <tr> <td>FTTR008</td> <td>Fraternal Nth</td> <td>1507188</td> <td>5333260</td> <td>583</td> <td>9.2</td> <td>2</td> <td>284</td> </tr> <tr> <td>FTTR009</td> <td>Fraternal Nth</td> <td>1507238</td> <td>5333483</td> <td>438</td> <td>10</td> <td>0</td> <td>67</td> </tr> </tbody> </table>										Trench	Zone	NZTM_E	NZTM_N	Elev	Length	Dip	Azimuth	FTTR001	Fraternal	1507244	5333083	541	8	0	281	FTTR002	Fraternal	1507237	5333081	543	1.5	0	189	FTTR003	Fraternal	1507235	5333167	519	7	0	273	FTTR004	Fraternal Nth	1507261	5333361	467	5	0	80	FTTR005	Fraternal	1507234	5333031	573	9.8	0	60	FTTR006	Fraternal	1507232	5333306	479	5.6	-40	110	FTTR007	Fraternal Nth	1507177	5333243	577	7.7	-20	95	FTTR008	Fraternal Nth	1507188	5333260	583	9.2	2	284	FTTR009	Fraternal Nth	1507238	5333483	438	10	0	67
Trench	Zone	NZTM_E	NZTM_N	Elev	Length	Dip	Azimuth																																																																																		
FTTR001	Fraternal	1507244	5333083	541	8	0	281																																																																																		
FTTR002	Fraternal	1507237	5333081	543	1.5	0	189																																																																																		
FTTR003	Fraternal	1507235	5333167	519	7	0	273																																																																																		
FTTR004	Fraternal Nth	1507261	5333361	467	5	0	80																																																																																		
FTTR005	Fraternal	1507234	5333031	573	9.8	0	60																																																																																		
FTTR006	Fraternal	1507232	5333306	479	5.6	-40	110																																																																																		
FTTR007	Fraternal Nth	1507177	5333243	577	7.7	-20	95																																																																																		
FTTR008	Fraternal Nth	1507188	5333260	583	9.2	2	284																																																																																		
FTTR009	Fraternal Nth	1507238	5333483	438	10	0	67																																																																																		

Criteria	JORC Code Explanation	Commentary								
		FTTR010	Fraternal	1507260	5332902	607	5.7	0	274	
		FTTR011	Fraternal	1507259	5332953	608	4	-5	109	
		FTTR012	Fraternal	1507267	5333411	468	7	0	265	
		FTTR013	Fraternal Nth	1507229	5333208	517	4.8	0	117	
		FTTR014	Fraternal Nth	1507228	5333509	442	2.7	0	70	
		FTTR015	Fraternal	1507250	5332956	621	11	5	108	
		FTTR016	Fraternal	1507258	5332985	597	10.5	-2	277	
		FTTR017	Fraternal	1507240	5333131	542	8	0	290	
		FTTR018	Fraternal	1507245	5333028	563	12.5	3	239	
		BZTR001	Bonanza East	1507179	5333140	538	17.5	0	226	
		BZTR002	Bonanza	1507147	5333152	504	5.2	17	273	
		BZTR003	Bonanza	1507165	5333226	520	6.6	-23	116	
		BZTR004	Bonanza	1507136	5333225	545	1.9	0	249	
		BZTR005	Bonanza	1507133	5333245	556	4	0	277	
		BZTR006	Bonanza	1507161	5333183	513	3.4	-38	95	
		BZTR007	Bonanza	1507132	5333135	539	6	-5	278	
		BZTR008	Bonanza East	1507188	5333260	583	9.2	5	275	
		BZTR009	Bonanza	1507238	5333483	438	10	-19	67	
		BZTR010	Bonanza East	1507135	5333133	531	3.7	-11	108	
		BZTR011	Bonanza East	1507140	5333104	540	5	27	272	
Data aggregation methods	<ul style="list-style-type: none"> <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</i> <i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i> <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i> 		<ul style="list-style-type: none"> The core is generally samples at 1 metre intervals, but slightly shorter or longer samples may be taken around geological contacts. For reporting of drill hole intercepts weighted average estimates are used based on a ~1.0 g/t Au cut-off. No top cuts are applied. In the calculation of significant intervals, no more than two metres of internal consecutive dilution (<0.5g/t) was included and only intercepts greater than 1.0g/t Au reported. Grades are compiled using length weighting. 							

Criteria	JORC Code Explanation	Commentary
<i>Relationship between mineralisation widths and intercept lengths</i>	<ul style="list-style-type: none"> • <i>These relationships are particularly important in the reporting of Exploration Results.</i> • <i>If the geometry of the mineralisation with respect to the drillhole angle is known, its nature should be reported.</i> • <i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known').</i> 	<ul style="list-style-type: none"> • Drillholes are reported as true widths if the geometry of the mineralisation is known or been constrained otherwise the results are reported as downhole lengths.
<i>Diagrams</i>	<ul style="list-style-type: none"> • <i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drillhole collar locations and appropriate sectional views.</i> 	<ul style="list-style-type: none"> • Plans, cross sections and long sections of trench and drillhole locations are included in the announcement.
<i>Balanced reporting</i>	<ul style="list-style-type: none"> • <i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i> 	<ul style="list-style-type: none"> • The exploration results include significant drilling results from OGL and SIREN. OGL data was compiled from NZPAM exploration database.
<i>Other substantive exploration data</i>	<ul style="list-style-type: none"> • <i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i> 	<ul style="list-style-type: none"> • No other exploration data reported.
<i>Further work</i>	<ul style="list-style-type: none"> • <i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i> 	<ul style="list-style-type: none"> • Drilling • Structural mapping • Ongoing soil sampling to the south towards Globe Progress • Ongoing Independent Lab re analysis of trench and drill core samples.

Criteria	JORC Code Explanation	Commentary
	<ul style="list-style-type: none"> Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	<ul style="list-style-type: none"> Drill testing of all four interpreted shoots; Fraternal, Fraternal North, Bonanza and Bonanza East

Section 3 - Estimation and Reporting of Mineral Resource

(Criteria listed in section 1, and where relevant in section 2, also apply to this section.)

Criteria	Explanation	Commentary
Database integrity	<p>Measures taken to ensure that data has not been corrupted by, for example, transcription or keying errors, between its initial collection and its use for Mineral Resource estimation purposes.</p> <p>Data validation procedures used.</p>	<ul style="list-style-type: none"> The database is stored in Microsoft Excel which has been validated by Siren using software (Leapfrog Geo). Random spot checks were completed between database and hard copies. Prior to using the drilling and trench data in the Mineral Resource Estimate (MRE), Siren undertook a database audit. Siren database checks included the following: <ul style="list-style-type: none"> - Checking for duplicate drill hole names and duplicate coordinates in the collar table. - Checking for missing drill holes in the collar, survey, assay, and geology tables based on drill hole names. - Checking for survey inconsistencies including dips and azimuths 90°, azimuths >360°, and negative depth values. - Checking for inconsistencies in the 'From' and 'To' fields of the assay and geology tables. - The inconsistency checks included the identification of negative values, overlapping intervals, duplicate intervals, gaps and intervals where the 'From' value is greater than the 'To' value in assay and geology tables. - Checking density data. The drill hole and trench data were considered suitable for underpinning the MRE of Inferred global Au and Sb resources as of 11 September 2024.
Site visits	<p>Comment on any site visits undertaken by the Competent Person and the outcome of those visits.</p> <p>If no site visits have been undertaken indicate why this is the case.</p>	<ul style="list-style-type: none"> The Competent Person has visited the site. The site visits included reviewing and supervision Siren core and core logging that was available on site as well as the ground over the mineral resource area which, drill supervision, involved spot checks on collar survey details. QAQC, geology modelling, and observations of mineralisation in the field and core.

Criteria	Explanation	Commentary
<p><i>Geological interpretation</i></p>	<p><i>Confidence in (or conversely, the uncertainty of) the geological interpretation of the mineral deposit.</i></p> <p><i>Nature of the data used and of any assumptions made.</i></p> <p><i>The effect, if any, of alternative interpretations on Mineral Resource estimation.</i></p> <p><i>The use of geology in guiding and controlling Mineral Resource estimation.</i></p> <p><i>The factors affecting continuity both of grade and geology.</i></p>	<ul style="list-style-type: none"> • Geological interpretation based on available field mapping data, structural mapping, trench & drillhole lithology and grade data. Modelling was completed using Leapfrog Geo modelling software. Wireframing and geological modelling was carried out by SIREN. • The Fraternal Shear is a steep west dipping hosting shear zone that appears structurally controlled within an anticline hinge zone. The controls on both Sb and Au plunge have yet to be determined. The variography suggests that the Sb grade plunges moderately to the north parallel to the interception of the Bonanza East and Fraternal mineralised shears. Au appears to plunge moderately to the south. • A cut-off grade of 0.5g/t AuEq was used to guide the geological continuity of the interpreted shear mineralisation. The cut-off grade was selected based on the reef shoot contact correlating with mineralisation greater than 0.5 g/t AuEq. Within the mineralised wireframe, if an intercept fell below the nominal cut-off but continuity was supported by host lithologies, the intercept was retained for continuity purposes due to the commodity and the style of deposit.

Criteria	Explanation	Commentary
<p><i>Dimensions</i></p>	<p><i>The extent and variability of the Mineral Resource expressed as length (along strike or otherwise), plan width, and depth below surface to the upper and lower limits of the Mineral Resource.</i></p>	<ul style="list-style-type: none"> • Fraternal MRE domain edges are set by grade, shape, spacing and continuity of geology, trenching and drilling. The domain extends half the average drill spacing along strike and down plunge. • Fraternal extends 250m along strike, averages 200 m down dip below the surface and varies from 0.5m-15m thick. • Bonanza East extends 260m along strike, averages 80m down dip below the surface and varies from 1m to 12m thick. The mineralised shear dip moderately to the east and intersects with the west dipping Fraternal shear. Antimony mineralisation appears to be concentrated around the intersection of the two shear zones.
<p><i>Estimation and modelling techniques</i></p>	<p><i>The nature and appropriateness of the estimation technique(s) applied and key assumptions, including treatment of extreme grade values, domaining, interpolation parameters and maximum distance of extrapolation from data points. If a computer assisted estimation method was chosen include a description of computer software and parameters used.</i></p> <p><i>The availability of check estimates, previous estimates and/or mine production records and whether the Mineral Resource estimate takes appropriate account of such data.</i></p> <p><i>The assumptions made regarding recovery of by-products.</i></p> <p><i>Estimation of deleterious elements or other non-grade variables of economic significance (e.g. sulphur for acid mine drainage characterisation).</i></p> <p><i>In the case of block model interpolation, the block size in relation to the average sample spacing and the search employed.</i></p> <p><i>Any assumptions behind modelling of selective mining units.</i></p>	<ul style="list-style-type: none"> • For this MRE, SIREN has completed the following: <ul style="list-style-type: none"> - <i>Geological interpretation and wireframing in Leapfrog Geo</i> - <i>Hard boundary compositing in Leapfrog – Edge Module (Leapfrog Edge);</i> - <i>Variography and Ordinary Kriging in Leapfrog Edge; and</i> - <i>Block Model Estimation in Leapfrog.</i> - <i>Block Model Validation in Leapfrog</i> • Composites were based on 1 m composites for Au and Sb. • Outlier grades were assessed by reviewing composite histograms of Au & Sb grade for each individual wireframe. An extreme outlier grade was identified in the Fraternal Au domain, and it was controlled during estimation by using Leapfrog's outlier tools. • The search distances, number of passes, minimum and maximum sample numbers were based on the variography model and Major and Semi-Major directions were around 75%-100% of the range of variogram models. 3 estimation passes were used for Au, and Sb. The first pass search was around 45 x 35 x 4 m. Each pass after that was extended by ~10-20%. • Sub-block model parent size was 10 x 10 x 5m based on domain geometry and drillhole spacing with sub-blocking to 1 x 5 x 2.5m. • The first pass used a minimum of 5 samples and maximum of 32 samples and a maximum of 4-5 samples per drill hole. The second pass used a minimum of 4 samples. The third pass used a minimum of 2 samples. • Cell discretization of 5 x 5 x 1 (X, Y, Z) was employed. • Block model validation included block statistics review, visual inspection of grade distribution against composites, domain boundary and estimation variable changes were undertaken.

Criteria	Explanation	Commentary
	<p><i>Any assumptions about correlation between variables.</i></p> <p><i>Description of how the geological interpretation was used to control the resource estimates.</i></p> <p><i>Discussion of basis for using or not using grade cutting or capping.</i></p> <p><i>The process of validation, the checking process used, the comparison of model data to drill hole data, and use of reconciliation data if available.</i></p>	<ul style="list-style-type: none"> • Arsenic is shown to be moderately positively correlated with gold grades and typical of refractory gold-pyrite-arsenopyrite mineralisation. • Au and Sb were estimated in this mineral resource and are correlatable. Sb appears to occur as a late-stage mineralisation phase hosted in brittle fractures and veinlets within the Au-hosting shear envelope. • Au and Sb were estimated, and the AuEq was calculated for each block based on these results. The formula used is $(AuEq = Au \text{ g/t} + 2.25 \times Sb \%)$. The formula is based on a gold price of US\$2,160 per ounce, antimony price of US\$15,625 per tonne and metal recoveries of 85% for gold and 85% for antimony.
Moisture	<p><i>Whether the tonnages are estimated on a dry basis or with natural moisture, and the method of determination of the moisture content.</i></p>	<ul style="list-style-type: none"> • All tonnages are based on dry bulk density measures. The mean of the bulk density measures was assigned to the block by mineralisation domains.
Cut-off parameters	<p><i>The basis of the adopted cut-off grade(s) or quality parameters applied.</i></p>	<ul style="list-style-type: none"> • The grade envelope was used for domaining using a lower cut-off of 0.5 g/t AuEq. This number was subjectively selected based on previous resource estimations completed by Siren in the Reefton Goldfield.
Mining factors or assumptions	<p><i>Assumptions made regarding possible mining methods, minimum mining dimensions and internal (or, if applicable, external) mining dilution. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential mining methods, but the assumptions made regarding mining methods and parameters when estimating Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the mining assumptions made.</i></p>	<ul style="list-style-type: none"> • No assumptions have been made regarding future mining methods.
Metallurgical factors or assumptions	<p><i>The basis for assumptions or predictions regarding metallurgical amenability. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential metallurgical methods, but the assumptions regarding metallurgical treatment processes and parameters made when reporting</i></p>	<ul style="list-style-type: none"> • Independent metallurgical test work undertaken in June-July 2024 on three composite samples derived from fresh Auld Creek diamond core from the Fraternal Shoot. The samples were sent to ALS Perth to test for both gold and antimony recovery into a flotation concentrate.

Criteria	Explanation	Commentary								
	<p><i>Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the metallurgical assumptions made.</i></p>	Sample No	Drill Hole	From	To	Au g/t	Sb %	As %	Mass kg	
		AC001	ACDDH005	59.39	63.27	3.0	0.08	0.31	27.3	
				75.07	76.37					
		AC002	ACDDH004	126.35	131.81	5.9	5.80	0.48	26.6	
		AC003	ACDDH004	120.10	125.14	4.1	1.35	0.38	27.0	
		<ul style="list-style-type: none"> The metallurgical results for gold indicate that the sample comprise refractory material that responds to flotation with recoveries ranging from 95-98% to a flotation concentrate product. The metallurgical results for antimony showed generally low flotation recoveries (71-90%) when CuSO₄ was used as an activator. However, when Pb(NO₃)₂ was used as the activator on AC003 the Sb recovery increased from 71.3 to 97.6%. 								
		Sample No	Au (g/t)	Au Flotation* Recovery (%)	Sb (%)	Sb Flotation* Recovery (%) (CuSO ₄)	Sb Flotation Recovery (%) Pb(NO ₃) ₂			
		AC001	3.0	95.8	0.08	89.7				
		AC002	5.9	98.3	5.80	64.6				
		AC003	4.1	97.8	1.35	71.3	97.6			
<p>* Kinetic Rougher test</p> <ul style="list-style-type: none"> No metallurgical recovery factors were applied to the MRE. 										
Environmental factors or assumptions	<p><i>Assumptions made regarding possible waste and process residue disposal options. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider the potential environmental impacts of the mining and processing operation. While at this stage the determination of potential</i></p>	<ul style="list-style-type: none"> Auld Creek Project lies within land that is administered by the Department of Conservation (DoC). The Globe Progress open cut gold mine 2km to the south, which was successfully operated by OGL between 2007 and 2016 is also contained within the Victoria Forest Park administered by DoC. The area is generally covered with beech forest with native scrub and sub-alpine grasslands. Some of the beech forest has been logged for timber for historic mining. 								

Criteria	Explanation	Commentary
	<p><i>environmental impacts, particularly for a greenfields project, may not always be well advanced, the status of early consideration of these potential environmental impacts should be reported. Where these aspects have not been considered this should be reported with an explanation of the environmental assumptions made.</i></p>	<ul style="list-style-type: none"> Siren has an Access Agreement with DoC which allows for 21 drill pads and a field camps and helicopter landing sites. No environmental factors were applied to the MRE. The deposit is located on an existing exploration permit.
Bulk density	<ul style="list-style-type: none"> <i>Whether assumed or determined. If assumed, the basis for the assumptions. If determined, the method used, whether wet or dry, the frequency of the measurements, the nature, size and representativeness of the samples.</i> <i>The bulk density for bulk material must have been measured by methods that adequately account for void spaces (vugs, porosity, etc.), moisture and differences between rock and alteration zones within the deposit.</i> <p><i>Discuss assumptions for bulk density estimates used in the evaluation process of the different materials.</i></p>	<ul style="list-style-type: none"> The dry bulk density value used in the MRE were assigned based on average values of the available density data from ACP as well as other SIREN Reefton projects. A mean of 2.65 t/m³ were used for oxide at the top of the model and 2.75 t/m³ for fresh rock. 106 density samples have been collected in the Auld Creek mineralisation units and in the host rocks. A total of 708 density samples have been collected by Siren in the Reefton Goldfeld in the same geology. Siren collects density samples routinely during logging of diamond drill core. Specific Gravity (SG) is calculated using the following formula: Weight in Air (Weight in Air – Weight in water) = SG.
Classification	<ul style="list-style-type: none"> <i>The basis for the classification of the Mineral Resources into varying confidence categories.</i> <i>Whether appropriate account has been taken of all relevant factors (i.e. relative confidence in tonnage/grade estimations, reliability of input data, confidence in continuity of geology and metal values, quality, quantity and distribution of the data).</i> 	<ul style="list-style-type: none"> Mineral Resources were classified as Inferred to appropriately represent confidence and risk with respect to data quality, drill hole spacing, geological and geostatistical, grade continuity and mineralisation volumes. Additional considerations were the stage of project assessment, amount of diamond drilling and trenching undertaken, current understanding of mineralisation controls and selectivity within an underground mining environment. In Siren opinion, the drilling, surveying and sampling undertaken, and analytical methods and quality controls used, are appropriate for the style of deposit under consideration. Inferred Mineral Resources were defined where a low to moderate level of geological confidence in geometry, continuity and grade was demonstrated. The reported Mineral Resource was constrained at depth by the available drill hole spacing outlined for Inferred classification,
	<ul style="list-style-type: none"> <i>Whether the result appropriately reflects the Competent Person's view of the deposit.</i> 	<ul style="list-style-type: none"> The data spacing, and distribution is sufficient to establish geological and grade continuity appropriate for MRE and the results appropriately reflect the Competent Person's view of the deposit.

Criteria	Explanation	Commentary
Audits or Reviews	<ul style="list-style-type: none"> <i>The results of any audits or reviews of Mineral Resource estimates.</i> 	<ul style="list-style-type: none"> Internal reviews of the MRE by SIREN were completed.
Discussion of relative accuracy/ confidence	<ul style="list-style-type: none"> <i>Where appropriate a statement of the relative accuracy and confidence level in the Mineral Resource estimate using an approach or procedure deemed appropriate by the Competent Person. For example, the application of statistical or geostatistical procedures to quantify the relative accuracy of the resource within stated confidence limits, or, if such an approach is not deemed appropriate, a qualitative discussion of the factors that could affect the relative accuracy and confidence of the estimate.</i> <i>The statement should specify whether it relates to global or local estimates, and, if local, state the relevant tonnages, which should be relevant to technical and economic evaluation. Documentation should include assumptions made and the procedures used.</i> <i>These statements of relative accuracy and confidence of the estimate should be compared with production data, where available.</i> 	<ul style="list-style-type: none"> Variances to the tonnage, grade, and metal tonnes of the Mineral Resource estimate are expected with further definition drilling. It is the opinion of the Competent Person that the classification criteria for Inferred Mineral Resources appropriately capture and communicate these variances and risks. The Mineral Resource estimate is considered fit for the purpose of drill targeting. The Mineral Resource Statement relates to global tonnage and grade estimates. No formal confidence intervals nor recoverable resources were undertaken or derived. Variography was completed for Au and Sb and used to influence the resource classification. The variogram models were interpreted as being isotropic along the plane of shoot mineralisation, with shorter ranges perpendicular to this plane of maximum continuity. Validation checks have been completed on raw data, composited data, model data and Resource estimates. The model validations checked to ensure data honouring. The validated data consists of no obvious anomalies which are not geologically sound. The mineralised zone is based on actual intersections. These intersections are checked against the drill hole data. Field geologist selections, and the Competent Person has independently checked laboratory sample data. The selections are sound and suitable to be used in the modelling and estimation process. Where the drill hole data showed that no Au existed, the mineralised zone was not created in these areas. Further drilling and structural analysis need to be completed to improve Resource classification of the Inferred Resource.